User:

Friday, 08/08/2008 11:24:18 AM

Linda Lacelle

Process Sheet

Customer

: CC-DAR01 Dart Aerospace Ltd.

Job Number **Estimate Number** : 41077

P.O. Number

: 10804

: 08/08/2008 This Issue

: NC Prsht Rev.

Checked & Approved By

First Issue

Previous Run

Written By

Comment

: // : 00015 Type

S.O. No. :

: MACHINED PARTS

Drawing Number

Project Number Drawing Revision

Drawing Name

Part Number

Material

Due Date

Qty:

1 Um:

Each

Additional Product

PRELIMINARY ISSUE

: PRELIM.

: D412777011

: D412-777-011

: 15/08/2008

Job Number:



Seq. #:

Machine Or Operation:

Description: PACKAGING RESOURCE #1

PACKAGING 1

Comment: PACKAGING RESOURCE #1

PICK PACKING KIT:

Para worl

Rubber Cushion

2.0

1.0

D2182B



Comment: Qty.: 12.0000 f(s)/Unit

Rubber Cushion

26 X D2182B055 (5.5")

D2274

Radius Block

12.0000 f(s)



Comment: Qtv.:

52.0000 Each(s)/Unit Total:

52.0000 Each(s)

D2521

Bearpaw 205

35062



5P

Comment: Qty.:

Washer

Bearpaw 205

Radius Block

2.0000 Each(s)/Unit

Total:

Total:

2.0000 Each(s)

D2529

Washer



Comment: Qty.:


12.0000 Each(s)/Unit

Total:

12.0000 Each(s)

Page 1

Form: rprocess



Date: Friday, 08/08/2008 11:24:18 AM User: Linda Lacelle **Process Sheet** Drawing Name: PRELIM. Customer: CC-DAR01 Dart Aerospace Ltd. Job Number: 41077 Part Number: D412777011 Job Number: Seq. #: **Machine Or Operation:** Description: 14.0 AN960JD416 Washer M108/61 Comment: Qty.: 52.0000 Each(s)/Unit Total: 52.0000 Each(s) Washer MS21042L4 Comment: Qty.: 60.0000 Each(s) TotaL Nut QC4 INSPECT 100% KITS FOR COMPLETENES **ENGINEERING** APPROVAL 1708,08,20 Comment: INSPECT 100% KITS FOR COMPLETENESS 17.0 **PACKAGING** PACKAGING RESOURCE #1 Comment: PACKAGING RESOURCE #1 PACKAGE PER PPP 41077 18.0 QC21 FINAL INSPECTION/W/O RELEASE Comment: FINAL INSPECTION/W/O RELEASE N 28.20 Job Completion RELEASED 08.09.08

Yabbonyr Englishing

DART AEROSPACE LTD.

- Position the D3695-1 FWD Ski Section and D3796-041 Wearplate as shown in Figure 1. 3.1.4
- The D2521 Bearpaw, D3795-1 Forward Ski Section and D3795-3 Mid Ski Section may be 3.1.3 relieved to clear the wearshoe mounting screws provided the relief leaves 0.375in thickness.
- Attach the D2947 Clamps, D2182B055 Rubber Cushion and associated hardware in the holes as 3.1.4 shown in Figure 3 and Section A-A. CAUTION: The torque on the nuts should be limited to 20 in-lb.
- Additional AN960JD416 washers may be installed under the nuts to ensure 1.5-4 threads in safety 3.1.5 on the bolts. Although not generally necessary, it is also acceptable to replace the AN4 bolts with longer or shorter AN4 bolts, if required.
- Lower the aircraft 3.1.6

4.0 WEIGHT AND BALANCE

			LATERAL		LONGITUDINAL	
Installation	Weight	Arm	Moment	Arm	Moment	
D412-777-011	72.0 lb 32.7 kg	0.0 in 0.0 m	0.0 lb-in 0.0 m-kg	115 in 2.93 m	8280 in-lb 95.8 m-kg	

5.0 PARTS LIST

QTY -011	PART NUMBER	DESCRIPTION
		BEARPAW INSTALLATION
X	D412-777-011	BEARFAW INSTALLATION
26	D2182B055	RUBBER CUSHION
52	D2274	RADIUS BLOCK
2	D2521	BEARPAW
12	D2529	WASHER
26	D2947	CLAMP
2	D3795-1	FWD SKI SECTION
2	D3795-3	MID SKI SECTION
2	D3796-041	FWD WEARPLATE
2	D3796-043	AFT WEARPLATE
8	AN4-12A	BOLT
52	AN4-17A	BOLT
8	AN970-4	WASHER
52	AN960JD416	WASHER
60	MS21042L4	NUT (OR MS21042-4)

• COPYRIGHT @ 2008 BY DART AEROSPACE LTD •

THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.

Revision: A

Date: 08.08.01

DART AEROSPACE LTD.

IIN-D412-777

Page 4 of 5

- The D2521 Bearpaw, D3795-1 Fwd Ski Section and D3795-3 Mid Ski Section may be 3.1.3 relieved to clear the wearshoe mounting screws provided the relief leaves 0.375in thickness.
- 3.1.4 Attach the D2947 Clamps, D2182B055 Rubber Cushion and associated hardware in the holes as shown in Figure 1 and Detail A, B and C. CAUTION: The torque on the nuts should be limited to 20 in-lb.
- 3.1.5 Additional AN960JD416 washers may be installed under the nuts to ensure 1.5-4 threads in safety on the bolts. Although not generally necessary, it is also acceptable to replace the AN4 bolts with longer or shorter AN4 bolts, if required.
- 3.1.6 Lower the aircraft

4.0 WEIGHT AND BALANCE

		LATERAL		LONGITUDINAL	
Installation	Weight	Arm	Moment	Arm	Moment
D412-777-011	72.0 lb	0.0 in	0.0 lb-in	123.7 in	8906 in-lb
Ski Installation	32.7 kg	0.0 m	0.0 m-kg	3.14 m	102.7 m-kg

5.0 PARTS LIST

QTY -011	PART NUMBER	DESCRIPTION
X	D412-777-011	SKI INSTALLATION
26	D2182B055	RUBBER CUSHION
52	D2274	RADIUS BLOCK
2	D2521	BEARPAW
12	D2529	WASHER
26	D2947	CLAMP
2	D3795-1	FWD SKI SECTION
2	D3795-3	MID SKI SECTION
2	D3796-041	FWD WEARPLATE
2	D3796-043	AFT WEARPLATE
8	AN4-12A	BOLT
52	AN4-184 PA 190801	JBOLT WASHER
8	AN970-4	
52	AN960JD416	WASHER
60	MS21042L4	NUT (OR MS21042-4)